LED-8090M 120W LED for HID Retrofit for Shoebox/Wallpack

Models

LED-8090MXX-A, 120-277VAC, ULus, 4000K or 5000K CCT, E39 LED-8090MXXC-A, 347VAC, cUL, 4000K or 5000K CCT, E39

Features


- > 120W LED Replaces 400W MH or HPS HID Lamps
- > Rotatable base enables user to accurately direct output to target
- > Designed for Horizontal installations
- > UL approved for damp environments and enclosed fixtures
- > Advanced active cooling: Active cooling and dynamic temperature control
- > 50,000 hour rated LED life (supported by LM80 and ISTMT reports (see website)
- > 5 Year Limited Warranty see website for details
- > UL1598C retains fixture UL Listing
- > Rated for enclosed fixture

Technical Specifications						
Models US/CAN	LED-8090M30-A	LED-8090M40-A	LED-8090M50-A	LED-8090M40C-A	LED-8090M50C-A	
	USA			Canada		
ССТ	3000K	4000K	5000K	4000K	5000K	
Power Consumption		120 watts				
Replaces		400 MH/HPS				
Mounting			E39	_		
Voltage	120-277VAC 347VAC			VAC		
LED Type	SAMSUNG 3030					
Beam Angle	Type V					
Dimmable	No					
Operating Temp	-40°F - +122°F					
Rated R70 Life	Up to 50,000 Hrs.					
Warranty	5 Year Limited*					
LM79 Specifications	Yes	Yes	Yes	Yes	Yes	
Power (W)	115.74	114.9	114.5	119.1	119.6	
ССТ	3037	3835	4915	3995	4956	
Light Output	10667	13312	13373	12293	12590	
Efficacy	87	101	105	103	105	
THD @ 277V	13.39%	12.45%	12.29%	13.30%	13.59%	
PF @ 277V	0.985	0.98	0.97	0.96	0.97	
CRI:	83	73	75	73	74	
R9	15	18	0	18	0	
Duv	0.0001	0.0008	0.0011	0.0008	0.0011	
Packaging	9 / Master Carton					
Unit	6.6"x 6.6"x 12.9" 2.9lbs.					
Master	20.7"x 18.5" x 13.8" 25.5 lbs.					






Type V



Lux Distance Curve



Installation Notes:

- · Ballast must be bypassed
- · Installing surge/lightning protectors is highly recommended

LED Power Consumption (Watts)	HID Power Consumption (Watts)	HID Ballast Power Consumption (Watts)	Total Savings (Watts)	Annual Energy Savings (14 hrs/day)	Lifetime Energy Savings (over 50,000 hrs)
120	400	80	360	\$202	\$1,980.00

Mounting Orientation		Minimum Fixture Size			
Base	Up	Base Down	Horiz	Requirements (inches)	
			4	Length	13.26
	TI TI			Width	6.33
		~~~		Height	6.33
				Cu. Inches	531.3
Approv	ved	Approved	Approved	cu. Inches	551.5



188 S. Northwest Highway • Cary, IL 60013 (847) 380-3540 • FAX: (847) 380-3542 www.led-llc.com



